

Produo Dispenser


PT1120 Product code: Product Finish: Chrome EAN13 barcode: 5060344156912



Product Features:


- Stylish dispenser delivering 98° (variable) filtered water
- Safety lock hot handle
- Scale inhibiting filter cartridge included
- 360° Swivel spout for maximum flexibility
- A modern design classic style
- 5 Year Warranty*
- WRAS approved

Product dimensions:



- Overall Height / projection: 299 mm
- Exit spout reach: 116 mm
- Exit spout height: 217 mm
- Base diameter(s): 48 mm
- Recommended hole diameter: Ø35 mm
- Max. surface depth: 50 mm
- Spout diameter: 24 mm
- Spout aerator size: M22x1 Male

Product flow characteristics:



- Min cold water pressure: 1.0 (no filter) / 1.5 (with filter) bar
- Min hot water pressure: 0.00 bar
- Recommended / Maximum domestic hot water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 4.45
- Control valve type: 1 x Ceramic disc HT diverter
- Product flow characteristics: Dual flow
- Aerator type: Neoperl aerator honeycomb, dual flow (01580900001) with brass adaptor adaptor for centre channel
- Hot and Cold inlet connections: flexi hose
- Non return valve(s): None

Care instructions summary:

- Clean the product regularly as required, using a mild soap and damp cloth, do not use any other
- cleaners, regular cleaning will prevent the build-up of lime scale and dirt Residues of sink & worktop cleaners can also cause damage to the mixer tap, so rinse with clean
- water after using, avoid contact with any abrasives
- Warranty Summary (Full details available on request):
- Mixer tap materials and workmanship defects warranted for 5 years
- Proboil2 materials and workmanship defects warranted for 2 years Mixer tap valves and working parts warranted for 5 years
- Surface finish warranty defects warranted for 1 year
- All o-rings, hoses & gaskets warranted for 1 year



*All temperatures quoted are measured within the tank of the boiler and actual spout exit temperature may vary dependant local conditions.

PROBOIL2 features:


- Compact size to fit discreetly into your base unit (Overall height 257mm, Width 217mm, Depth 175mm)
- Filtered water inlet
- 98 degree water outlet
- Safety steam vent to a standard dishwasher connection
- Removable tank lid for easy access, cleaning and descale
- 2 Litre tank
- Boiler can be floor or wall mounted
- UK manufactured boiler
- 2 Year Warranty*
- WRAS approval pending

For further information refer to proboil.co.uk and our user guide.

Our premium quality PROBOIL2 filter offers the following benefits:

- Filtered 98°C drinking water, engineered specifically for hot water applications
- Included with every PROBOIL2 system
- Recommended / Maximum replacement interval: 6 / 12 months
- Chlorine taste and odour reduction.
- Inbuilt corrosion protection
- Mineral adaption and scale reduction for protection
- · Reduces scaling potential of the water
- WRAS approved





The complete package:

Each **PRO**NTEAU system includes:

- A stylish PRONTEAU Dispenser
- PROBOIL2 hot water boiler
- PROBOIL2 scale control filter & assembly
- · Connecting hoses and safety vent
- Comprehensive user and installation guide
- Waste Plumbing Attachments
- Nationwide professional maintenance and service support

WATER THE WAY YOU WANT IT