

# **PROJECT 3 Part Mixer**


Product code: PT1009-2 Product Finish: Chrome EAN13 barcode: 5060879990722



#### **Product features:**

- Stylish 4 way mixer tap delivering domestic hot and cold, ambient and 80-98° filtered water.
- Suppled with 2 x patent pending proximity Hotkey  $^{\text{\tiny{TM}}}$  activation for 80-98° water, without the Hotkey™ the product reverts to a family safe 3 way mixer.
- 360° rotating thermally insulated spout
- Ceramic disc 1/4 turn smooth action control valves
- Hands free dispensing of 80-98° water possible for heavy pans
- Anti splash aerator as standard

#### **Product dimensions:**



• Overall Height / projection: 330 mm

• Exit reach: 220 mm • Exit height: 220 mm

• Centre distance(s): 90 - 180


• Base diameter(s): 45 x 45 x 45 mm • Recommended hole diameter: Ø35 mm

• Max. surface depth: 50 mm

• Spout diameter: 24 mm

• Spout aerator size: M22x1 Male

## **Product flow characteristics:**



- Min / Max water pressure: 0.75 / 5.5 bar (mixertap only)
- Recommended / Max incoming domestic hot water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 9.97
- Control valve type: 1 x Ceramic disc QT hot, 1 x Diverter Cold/Filter
- Product flow characteristics: (C,H&F/Boiling) dual flow
- · Aerator type: Neoperl aerator honeycomb dual flow
- Hot and Cold inlet connections: M10 x 1/2" M x 365mm flexi hose
- Non return valve(s): Yes, integral to hot and cold supplies

#### Care instructions summary:

- Clean the product regularly as required, using a mild soap and damp cloth, do not use any other cleaners, regular cleaning will prevent the build-up of lime scale and dirt.

  Residues of sink & worktop cleaners can also cause damage to the mixer tap, so rinse with
- clean water after using, avoid contact with any abrasives.
- Proboil4e requires periodic filter change and descaling, see user guide for detail

### Warranty Summary (Full details available on request):

- Mixer tap Materials and workmanship defects warranted for 5 years Proboil4e Materials and workmanship defects warranted for 2 years
- Mixer tap valves and working parts warranted for 5 years
- Surface finish warranty defects warranted for 1 year All O-rings, hoses & gaskets warranted for 1 year



\*All temperatures quoted are measured within the tank of the boiler and actual spout exit temperature may vary dependant on local conditions.

#### **PROBOIL.4E** features:

- Controllable tank temperature range from 75°C (holiday/eco mode) to 85,90,95,96, 97, 98°C using the touch screen controls.
- 4 Litre capacity tank, apx. 9 minutes reboil after use
- On screen filter life / replacement indicator
- Intelligent self-diagnostic control
- No external drain connection needed for a simplified and more flexible installation
- Flow limited to 2 litres/min to limit splashing and ensure a smooth flow
- Tool free, hand tight connectors to speed up installation, maintenance and descaling
- Compact size 20.6x25.6x29.1cm (excludes connections)
- 2 Year Warranty\*
- WRAS approval pending

For further information refer to proboil.co.uk and our user guides.



Our premium quality PROBOIL filter offers the following benefits:

- Filtered ambient and 80-98°C drinking water, engineered specifically for hot and ambient water applications
- Included with every **PRO**BOIL system
- 6 month life (based on 19 degrees Clark (London average hardness) and 5 litres per day usage)
- Free filter cartridge recycle scheme
- Superfine 5 micron carbon block filtration
- Chlorine taste and odour reduction.
- pH balanced delivery
- Adjustable hardness settings allows optimised filter life and boiler scale protection in both hard and soft water areas
- Inbuilt corrosion protection
- Mineral adaption and scale reduction for protection
- Simple quarter turn bayonet installation
- Automated on screen life reminder



## The complete package:

Each **PRONT**EAU system includes:

- A stylish choice of intelligent 4 way PRONTEAU mixer taps
- 2 x 4 way mixer tap Hotkeys
- PROBOIL.4E hot water boiler
- PROBOIL advanced scale control filter
- · Comprehensive user and installation guide
- Nationwide professional maintenance and service support

WATER THE WAY YOU WANT IT